

Ord 657  
Amend 728  
P.p 1507

An ordinance to amend Section 9 of Ordinance No. 468 entitled "An ordinance relating to the construction of sidewalks and curbing within certain limits in the City of Albany and repealing all ordinances and parts of ordinances in conflict herewith," passed by the Council November 10, 1908, approved by the Mayor November 11, 1908.

The People of the City of Albany do Ordain As Follows:

Section 1. That Section 9 of Ordinance No. 468 entitled "An ordinance relating to the construction of sidewalks and curbing within certain limits in the City of Albany and repealing all ordinances and parts of ordinances in conflict herewith," passed by the Council November 10, 1908, approved by the Mayor November 11, 1908, and the same is hereby amended so as to read as follows:

Section 9. Along the front of the sidewalk provided for in this ordinance shall be placed a curb of artificial stone or cement twelve feet wide and shall with the front line of the lot or block to the outer edge of the curbing which the said sidewalk is constructed, and said curb shall not be less than seven inches wide at the bottom and five inches wide at the top, and not less than eight inches deep, with the inner side perfectly circular, and each section of such curb shall not be less than five feet in length, except that the curb on Montgometry Street shall be constructed or laid nine feet from the lot line to outer edge of the curb and the curbs mentioned in Section 7 of this ordinance shall be eight feet from said lot line to outer edge of the curb and ten inches deep.

And all sidewalks and curbing provided for in this ordinance if constructed of cement and concrete shall consist of eight parts of gravel and two parts of cement for the base thereof, and concrete base for sidewalks to be not less than four inches thick and to be laid upon a bed of gravel not less than three inches thick and the top dressing of said sidewalks and outer surface and top of said curbing shall be not less than three-fourths of an inch thick and composed of six to ten percent sand and fifty percent cement, and sidewalk to have a slope of one-fourth of an inch to the front surface inside of said sidewalk to the outer edge of said curb, and at the street corners the same shall be required to conform to the quadrant of a circle with a thirty inch radius and at the other corners of the sidewalk to be rounded to conform to the quadrant of a circle with a twenty-four inch radius.

That all cement used as herein set forth, shall be of the best quality of Portland Cement and that the top surface

of all cement work constructed in dry weather, shall be kept wet for at least four days by a covering of wet sand one half inch thick.

Passed the council July 23 1913

Attest:

F. E. Van Tassel  
Recorder of the City of Albany.

Approved July 23 1913.  
C. S. Dickson  
Mayor.

**CITY RECORDER'S CERTIFICATE**

STATE OF OREGON. }  
COUNTY OF LINN. } ss.

I, F. E. Van Tassel, Recorder of the City of Albany, in Linn County, and State of Oregon, do hereby certify that the foregoing and annexed copy of.....  
Ordinance 457  
has been by me carefully compared with the original Bill No. 724  
now on file in my office, and that it is a true and correct copy of all and the whole of said  
Ordinance 457 as passed by the Council of the City of Albany, Oregon, July 23, 1913.

Witness, my hand and official signature and the seal of the City of Albany, this  
23rd day of July 1913

F. E. Van Tassel  
Recorder of the City of Albany.