

NOTES

- 1. PROVIDE PROTECTION FROM ALL VEHICLE TRAFFIC, EQUIPMENT STAGING, AND FOOT TRAFFIC IN PROPOSED FACILITY AREAS PRIOR TO, DURING, AND AFTER CONSTRUCTION.
- 2. PROVIDE PROTECTION FROM ALL VEHICLE TRAFFIC, EQUIPMENT STAGING, AND FOOT TRAFFIC IN PROPOSED FACILITY AREAS PRIOR TO, DURING, AND AFTER CONSTRUCTION.
- 3. GROWING MEDIUM SHALL BE PLACED IN EVEN LIFTS NO GREATER THAN 8 INCHES IN DEPTH, AS MEASURED LOOSELY. LIFTS SHALL BE MODERATELY COMPACTED BY USE OF A SAND OR WATER FILLED LAWN ROLLER. MECHANICAL COMPACTION WITH JUMPING JACKS OR SIMILAR EQUIPMENT IS PROHIBITED.
- 4. GROWING MEDIUM IN EACH FACILITY SHALL BE PLACED AND SHAPED THE SAME DAY AND IMMEDIATELY UPON COMPLETION ITS SURFACE SHALL BE PROTECTED WITH STRAW MATTING OR JUTE MATTING.
- 5. IMPERMEABLE LINER SHALL BE USED ONLY IF REQUIRED ON PROJECT PLANS.
- 6. VEGETATION: INSTALL PER PLANTING SCHEDULE.

7. IN UNLINED FACILITIES, BOTTOM OF PERFORATED DRAIN PIPE SHALL BE SET AT 2 1/2" ABOVE EXISTING SUBGRADE. IN LINED FACILITIES, BOTTOM PERFORATED DRAIN PIPE SHALL BE SET AT BASE OF DRAIN ROCK LAYER.

CITY OF ALBANY, OREGON PUBLIC WORKS DEPARTMENT

CURB EXTENSION PLANTER & POD SECTION VIEWS

NO SCALE

JANUARY 2015

NO. 608